



Initio Bullet 4MP

Vandalproof Bullet Camera with IR and varifocal lens



CAMERA

Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR
Day & Night	yes
WDR	Intellio WDR mode: 120dB

IMAGE

Focal length	2.8 to 12 mm
FOV	horizontal: 104° to 29°, vertical: 55° to 17°
Max. Resolution	2688 × 1520
Stream	50Hz: 25fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080) 60Hz: 30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080)
Day/Night Switch	Auto / Schedule / Triggered by alarm in

COMPRESSION

Video Compression	H.265 / H.264 / MJPEG
Video Bit Rate	256 Kbps to 16 Mbps
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2 / PCM
Audio Bit Rate	64Kbps (G.711) / 16Kbps (G.722.1) / 16Kbps (G.726) / 32-160Kbps (MP2L2)

INTERFACE

Communication Interface	1x RJ45 10M/100M Ethernet port
IO port	Audio I/O; Alarm I/O
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB

NETWORK

Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Client	Intellio Video System 4

GENERAL

Operating Conditions	-30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)
Power Supply / Consumption	12 VDC / 1.2A, max. 14.5W PoE (802.3at, 42.5V - 57V), 0.43A - 0.3A, max. 18W
Protection Level	IP67, IK10, TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection
Weight	1740 g

IR ILLIMINATION

IR Range	50 m
Wavelength	850 nm

INTELLIGENT VIDEO

Built in intelligence	Line crossing detection, intrusion detection
-----------------------	--

DIMENSIONS

